

**POLIOLEFINA**



Referencia			Antes	Después		Embalaje (m)	
	mm	Pul	D. Interno (mm)	D. Interno (mm)	Espesor (mm)	Tiras	Rollos
POL-12	0.8	3/64	1.1	0.50	0.22	1	200
POL-16	1.0	1/16	1.5	0.65	0.28	1	200
POL-24	2.0	3/32	2.5	1.00	0.35	1	200
POL-32	3.0	1/8	3.5	1.50	0.40	1	200
POL-48	4.5	3/16	5.0	2.30	0.50	1	200
POL-64	6.0	1/4	6.5	3.0	0.55	1	100
POL-75	7.0	5/16	7.5	3.5	0.55	1	100
POL-95	9.0	3/8	9.5	4.5	0.60	1	100
POL-127	12.0	1/2	12.5	6.0	0.60	1	100
POL-160	15.0	5/8	15.5	7.5	0.70	1	100
POL-190	18.0	3/4	19.0	9.0	0.80	1	100
POL-254	25.0	1	26.0	12.5	0.90	1	50
POL-320	30.0	1-1/4	31.5	15.0	0.95	1	50
POL-480	40.0	1-1/2	41.5	20.0	1.00	1	50
POL-508	50.0	2	≥50	25.0	1.00	1	25
POL-762	80.0	3	≥80	41.0	1.46	1	25
POL-1016	100.0	4	≥100	51.0	1.46	1	25

Características

1. Flexible
2. Cero halógenos
3. Retardado a la llama
4. Escasa generación de humo
5. Temperatura continua: -45° a 125°
6. Temperatura de contracción: 120°
7. Cumple RoHS